

PRODUCT DATA SHEET

MS DRAIN

Product Code: DMS233



Delta MS Drain is a dimpled sheet which also serves as a drainage layer thanks to its fused-on geotextile.

The sheet features a high compressive strength of c. 500kN/m² as well as more than 8,900 dimples/m², which ensures the best possible distribution of pressure on the substrate. It protects the perimeter insulation and the waterproofing of the cellar wall from damage as well as from surface and seepage water.

info@deltamembranes.com

www.deltamembranes.com

01992 523 523





BENEFITS

- The sheet features a high compressive strength of c. 500kN/m² as well as more than 8,900 dimples/m², which ensures the best possible distribution of pressure on the substrate. It protects the perimeter insulation and the waterproofing of the cellar wall from damage as well as from surface and seepage water.
- At c. 0.6L/s x m, the drainage capacity of the MS Drain is nearly twice that demanded by DIN 4095. The material of the dimpled sheet is 100% free from recycling products and uncontaminated. It may be installed at depths of up to 10 metres.



SPECIFICATION

- NBS Specification J40 295A flexible sheet tanking/damp proofing



ASSOCIATED PRODUCTS

- Koster Waterproofing
- Delta Terraxx-Schraube
- Delta MS Profile
- Delta Haftangel (self- adhesive pins)

PRODUCT DATA SHEET

MS DRAIN

Product Code: DMS233

TECHNICAL DATA

Material high-density polyethylene

Dimple height approx 4mm

Air Gap Approx 2,6 L/m²

Characteristics opening size approx 0,06mm

Drainage capacity approx. 0,6 L/s · m²

Compressive strength approx. 500 kN/m²

CE Conformity DIN EN 13252

Roll Size 30 m x 2 m

